



## TECHNICAL PARAMETERS

Input [V]	Welding current [A]	Duty cycle MIG [%]	Wire feeder	Welding wire spool [kg]/[mm]	Wire diameter [mm]	Weight [kg]	Dimensions [mm]
400	MIG 50 – 250 TIG 10 – 250 MMA 10 – 220	60	built-in, 4 - roll gear	≤ 15 / Ø200/300	0.8 / 1.0 / 1.2	38	920 × 470 × 740

**Additional features:** 2T/4T, inductance, polarity change, HOT START, ARC FORCE, VRD

## DESCRIPTION


**SPARTUS® EasyMIG 270** is modern, inverter and professional MIG/MAG welding machine with inert or active gas shielding and MMA coated electrode welding. **SPARTUS® EasyMIG 270** is powered by 400V three-phase. The maximum welding current for **SPARTUS® EasyMIG 270** is 250A for MIG/MAG and 230A for MMA. 60% high working cycle ensures stable output parameters during long-term welding work. **SPARTUS® EasyMIG 270** is equipped in the synergy system for MIG/MAG welding with the ability to manually change parameters. You can choose the following programs: CO<sub>2</sub> steel, mixed steel, core wire welding. Making the synergy correction is signalled by flashing LED on the device's panel. **SPARTUS® EasyMIG 270** is a compact device designed mostly for efficient welding of steel constructions and working in difficult workshop conditions.

## WIRE FEEDER

Professional four-roller feeder ensures stable welding wire feed. Resistant, robust and compact design makes it perfect equipment for difficult conditions, and there is a possibility of mounting a technical gas cylinder on the chassis of the device.



SPARTUS® EasyMIG 270



EASY

### PACKAGE EQUIPMENT:

- MIG gun SPARTUS® SPE 240 3m
- MIG toolbox (consumable kit)
- passive helmet SPARTUS® Easy with flap
- electrode holder
- work clamp
- gas hose
- user's manual

